

Declaration of performance

for the product

Multiprotec Absolute 3 in 1



| | | |
|----|---|--|
| 1. | Unique identification code of the product-type | |
| | 5905167816868 - Multiprotec Absolute 3 in 1 | |

| | | |
|----|---|-------------------|
| 2. | Type, batch or serial number or any other element allowing identification of the construction product as required under: | |
| | EAN | 5 905 167 816 868 |

| | | |
|----|--|--|
| 3. | Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as fore | |
| | Insulating material for the acoustic use under floating floors | |

| | | |
|----|---|--|
| 4. | Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant: | |
| | Decora S.A. ; Prądzyńskiego 24a; 63-000 Środa Wielkopolska; Poland | |

| | | |
|----|---|--|
| 5. | Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): | |
| | Not Applicable | |

| | | |
|----|---|--|
| 6. | System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex | |
| | System number - 4 | |

| | | |
|----|---|--|
| 7. | In case of the declaration of performance concerning a construction product covered by a harmonised standard | |
| | No synchronized standard | |

| 8. Declared performance | | | | | |
|-------------------------|--|-------------|-----------|----------------------|----------------------------------|
| Symbol | Parameter | Value | | Unit | Norm |
| T | Thickness | 3 | +/- 0,15 | [mm] | EN 823:2013 |
| L | Length | 5000 | -0% + 5% | [mm] | EN 822:2013 |
| W | Width | 1000 | -1% +2,5% | [mm] | EN 822:2013 |
| Q | Squareness | ≤ 4 | 0 | [mm/m] | EN 824:2013 |
| S | Flatness | ≤ 1 | 0 | [mm/m] | EN 825:2013 |
| AW | Surface mass | 1,95 | +/- 10% | [kg/m ²] | EN ISO 23997:2012 |
| QW | Density | 900 | +/- 10% | [kg/m ³] | EN 1602 |
| RWS | Reflected walking sound | 28 | +/-2 | [%] | CEN/TS 16354:2013, EPLF 021029-3 |
| IS | Impact sound improvement | 19 | +/-2 | [dB] | EN ISO 10140:2007 |
| CS | Compressive strength at 0.5 mm compression | 100 | +/- 10% | [kPa] | EN 826:2013 |
| CC | Static compressive strength | 50 | +/- 10% | [kPa] | EN 1606:2013 |
| DL | Dynamic compressive strength | > 2 500 000 | | [cycles] | EN 13793:2014 |
| PC | punctual conformability | 2,3 | +/- 10% | [mm] | EN ISO 868:2005 |
| TR | Thermal Resistance | 0,01 | +/- 0,003 | [m ² k/W] | EN 12664:2002 |
| SD | sD-value | >150 | | [m] | EN 12086:2013 |
| RLB | Resistance to Large Ball | ≤ 1000 | | [mm] | EN 438-2:2016 |
| RTF | Reaction on fire | Bfl - s1 | | [-] | EN 13501-1:2010 |

| | | |
|----|---|--|
| 9. | The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. | |
| | <i>This declaration of performance is issued under the sole responsibility of the manufacturer</i> | |

| | |
|-------------------|------------------|
| creation date | 2021-12-02 |
| modification date | 2021-12-02 |
| Printed | 10.01.2022 13:48 |